



MARKED-UP COPY OF
ORIGINAL SPECIFICATION

S. N. 10/695,813
Examiner S. Moon
Group Art Unit 2629

DRIVING CIRCUIT FOR SOLVING COLOR DISPERSION

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a display driving circuit and, more
5 particularly, to a driving circuit for solving color dispersion and a reference
voltage generator thereof.

2. Description of Related Art

Because CRTs have huge volumes and generate radiation, they are
increasingly replaced by flat panel displays. A liquid crystal planar display,
10 which drives display cells of the display panel using voltage-driving, is
mostly popular in current market. Each pixel on the display panel is
controlled by three primary colors R (red), G (green) and B (blue). The
three primary colors have different optical features and thus require
different curves for operating voltages and brightness. FIG. 1a shows a
15 graph of operating voltage to resolution curves respectively to the three
primary colors, and FIG. 1b shows a graph of brightness to resolution curves,
which are Gamma curves respectively for the three primary colors with
different operating voltages.

However, upon design consideration, flat panel displays in current
20 market apply a same operating voltage to R, G, B colors; i.e., data drivers

(source drivers) are provided with a same Gamma curve (as shown in FIG. 1c) to drive R, G, B sub-pixels, so that brightness of pixels on display panel presents error with respect to original brightness and thus the displays present color dispersion. For current techniques, an operating voltage is
5 provided by voltage regulator and variable resistor. In case of provision of three different operating voltages, consumption of voltage regulator and variable resistor must be increased by three times, thus requiring large space and increasing power dissipation.

Therefore, it is desirable to provide an improved driving circuit
10 capable of concurrently offering Gamma curves for R, G, B colors, to mitigate and/or obviate the aforementioned problems.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a driving circuit for solving color dispersion and a reference voltage generator thereof, which
15 can effectively avoid color dispersion to increase display quality.

Another object of the present invention is to provide a driving circuit for solving color dispersion and a reference voltage generator thereof, which can provide three separate and regulable Gamma reference voltages.

To achieve the objects, the driving circuit for solving color
20 dispersion is implemented in a flat panel display with a plurality of display

MARKED-UP COPY OF
ORIGINAL SPECIFICATION

S. N. 10/695,813

Examiner S. Moon
Group Art Unit 2629

cells. The driving circuit includes a coding unit, a reference voltage generator and a driving unit. The coding unit generates a plurality of ~~encoded~~encoded data according to a plurality of characteristic curves. The reference voltage generator receives the ~~encoded~~encoded data and converts
5 the ~~encoded~~encoded data into a plurality of reference voltages. The driving unit receives the reference voltages and accordingly drives the display cells.

Other objects, advantages, and novel features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

10 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1a is a schematic graph of typical operating voltage to resolution curves respectively to R, G, B colors;

FIG. 1b is a schematic graph of typical brightness to resolution curves respectively to different R, G, B operating voltages;

15 FIG. 1c is a schematic graph of a typical Gamma curve;

FIG. 2 is a schematic diagram of functional blocks in accordance with a preferred embodiment of the invention;

FIG. 3 is a schematic diagram of functional blocks inside the reference voltage generator of FIG. 2; and

20 FIG. 4 is an embodied timing diagram in accordance with the

invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to functional blocks of FIG. 2, there is shown a preferred embodiment of a driving circuit for solving color dispersion. In
5 FIG. 2, the driving circuit essentially includes a coding unit 21, a reference voltage generator 22 and a data driver 23. The coding unit 21 generates a plurality of ~~encoded~~encoded data according to Gamma curves of three primary colors. Positive and negative polarities of the Gamma curves are respectively divided into a plurality of selection voltages. In this
10 embodiment, the number of selection voltages is 128, each having a range of about 39 mV, which is ~~encoded~~encoded by 7 bits, thus using ~~an~~an ~~encoded~~encoded data derived from the 7 bits can select a desired voltage.

The reference voltage generator 22 receives the ~~encoded~~encoded data and applies the same to digital-to-analog conversion in order to generate a
15 plurality of RGB Gamma reference voltages. FIG. 3 shows functional blocks inside the reference voltage generator 22 of FIG. 2. In FIG. 3, the reference voltage generator 22 essentially includes a plurality of sample/latch units 221, 222, 223, a plurality of digital-to-analog converters 224, 225, 226 and a plurality of buffers 227, 228, 229. There are two
20 control signal lines 231, 232 between each sample/latch unit and

MARKED-UP COPY OF
ORIGINAL SPECIFICATION

S. N. 10/695,813

Examiner S. Moon
Group Art Unit 2629

digital-to-analog converter.

The sample/latch units 221, 222, 223 receive encoded data generated by the coding units respectively, sample/latch the encoded data and transmit the encoded data to corresponding digital-to-analog converters through corresponding control signal lines 231, 232. FIG. 4 shows a timing of data input via the control signal lines 231, 232 of FIG. 3. In FIG. 4, the control signal line 231 is regarded as an address line and the control signal line 232 is regarded as a data line to transmit data (~~encoded~~encoded value) with 7 bits.

Referring to FIGS. 2 and 3 at the same time, the digital-to-analog converters 224, 225, 226 receive the ~~encoded~~encoded values and convert the same from digital to analog to thus generate a plurality of reference voltages, each corresponding to Gamma curve of a primary color. The buffers 227, 228, 229 enhance amplitudes of the reference voltages for outputting to the data driver 23. Thus, the data driver 23 can drive R, G, B subpixels (not shown in figure) on display panel based on Gamma reference voltages of three primary colors R, G, B, such that brightness of the subpixels can accurately be presented. Therefore, it is prevented that brightness of pixels on display panel presents error with respect to original brightness and further the displays present color dispersion.

MARKED-UP COPY OF
ORIGINAL SPECIFICATION

S. N. 10/695,813

Examiner S. Moon

Group Art Unit 2629

In view of the foregoing, it is known that the invention can generate different encoded data based on Gamma curves derived from different primary colors and convert the encoded data into analog form from digital form, thus obtaining Gamma reference voltages of three primary colors for provision to the data driver. The data driver accordingly displays accurate
5 brightness of pixels on display panel. Thus, color dispersion presented on display is solved and display quality is increased. In addition, three separate and regulable Gamma reference voltages are also provided.

Although the present invention has been explained in relation to its
10 preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of the invention as hereinafter claimed.

MARKED-UP COPY OF
ORIGINAL SPECIFICATION

S. N. 10/695,813

Examiner S. Moon
Group Art Unit 2629

ABSTRACT OF THE DISCLOSURE

A driving circuit for solving color dispersion is disclosed, which includes a coding unit, a reference voltage generator and at least one data driver. The coding unit generates a plurality of ~~encoded~~encoded data based on
5 three Gamma curves. The reference voltage generator receives the ~~encoded~~encoded data and converts the ~~encoded~~encoded data into a plurality of reference voltages, such that the data driver drives display cells on the display array in accordance with the reference voltages.